

FIRE FIGHTER I JPR: FFI-5A

Candidate:

STANDARD: 4.5.1 NFPA 1001, 2019 Edition			Task: Clean and check ladders, ventilation equipment, SCBA, ropes, salvage equipment, and hand tools, given cleaning tools, cleaning supplies, and an assignment, so that equipment is clean and maintained according to manufacturer's or departmental guidelines, maintenance is recorded, and						
Preparedness, and Maintenance		Iaintenance	equipment is placed in a ready state or reported otherwise.						
PERFORMANCE equipment, follow OUTCOME: Safety: A safety v		equipment, follow	Il demonstrate the ability to select correct tools for various parts and pieces of guidelines, and complete recording and reporting procedures. violation is grounds for automatic failure. All proctors present shall review						
	Equipment Required: Ladders, rope, salvage equipment, ventilation equipment, hand tools, SCBA, service tags, and cleaning supplies.								
CONDITIONS: Given firefighting equipment, the candidate shall demonstrate the ability to:									
No.			Task Steps	\checkmark					
	EQUIPMENT TO BE CLEANED AND INSPECTED								
		(80	SCBA Mandatory & Check One Other):						
	SCBA	A	Hand Tool Ventilation Equipment						
	Ladde	er	Rope Salvage Equipment						
	SCBA								
1.	Inspect / Cl	ean face piece accor	rding to department policies.						
2.	Inspect / Clean back plate/frame/harness assembly according to department policies.								
3.	Inspect / Clean cylinder.								
4.	Place in ready state or report any deficiencies.								
	Hand Tools								
	Wooden / F	Fiberglass Handles:	:						
1.	Inspect Handle.								
2.	Inspect Head / Cutting edge / Surface.								
3.	Clean Tool.								
4.	Place in ready state or report any deficiencies.								

No.	Task Steps	 ✓ 					
	Ventilation Equipment - PICK ONE						
	Fueled						
1.	Check fuel level.						
2.	Check that appropriate guards are in place.						
3.	Check starting.						
4.	Place in ready state and report any deficiencies.						
	Electric						
1.	Check electric cords for damage if applicable.						
2.	Check that appropriate guards are in place.						
3.	Check starting.						
4.	Place in ready state and report any deficiencies.						
	Ladders						
1.	Clean Ladder.						
2.	Examine all beams, guides, halyard, cable, pawls, pulleys, rails, rungs, bolts, rivets, welds, heat indicator, and movable parts.						
3.	Place in ready state and report any deficiencies.						
	Rope						
1.	Clean rope.						
2.	Visually and physically inspect rope for damage.						
3.	Place in ready state and report any deficiencies.						
	Salvage Equipment						
1.	Clean provided salvage equipment.						
2.	Inspect equipment and identify damage.						
3.	Place in ready state and report any deficiencies.						

Evaluator (Print & Sign)

Date:



FIRE FIGHTER I JPR: FFI-5B

Candidate:

STANDARD: 4.5.2			Task: Clean, inspect, and return fire hose to service, given washing equipment,						
NFPA 1001, 2019 Edition			water, detergent, tools, and replacement gaskets, so that damage is noted and corrected, the hose is clean, and the equipment is placed in a ready state for						
Preparedness, and Maintenance			service.						
PERFORMANCE OUTCOME: and drying equipn and reload hose.		Ill demonstrate the ability to clean different types of hose, operate hose washing nent (if available), mark defective hose, and replace coupling gaskets, roll hose, violation is grounds for automatic failure. All proctors present shall review on.							
(if avail	Equipment Required: Fire apparatus, scrub brush, hose, cleaning supplies, replacement gaskets, hose washer and dryer (if available), log book or tags for reporting repair needs, and personal protective clothing (proctor to determine what PPE is to be worn).								
COND	CONDITIONS: Given Fire Department hose and apparatus, the candidate shall demonstrate the ability to:								
	Task Steps								
No.			Task Steps		✓				
No.	INSPECT / (CLEAN HOSE	Task Steps		 ✓ 				
No.	INSPECT / O Inspect / Cl		Task Steps						
	Inspect / Cl	ean hose.	Task Steps	ies.					
1.	Inspect / Cl	ean hose.	-	ies.					
1. 2.	Inspect / Cl Inspect / Cl Dry hose.	ean hose.	ling to department guidelin	es.					
1. 2. 3.	Inspect / Cl Inspect / Cl Dry hose. Place in rea	ean hose. ean couplings accord	ling to department guidelinnny deficiencies.	ies.					
1. 2. 3. 4.	Inspect / Cl Inspect / Cl Dry hose. Place in rea	ean hose. ean couplings accord dy state and report a G HOSE TO SERV	ling to department guidelinnny deficiencies.						
1. 2. 3.	Inspect / Cl Inspect / Cl Dry hose. Place in rea	ean hose. ean couplings accord dy state and report a G HOSE TO SERV	ling to department guidelinny deficiencies.						
1. 2. 3. 4.	Inspect / Cl Inspect / Cl Dry hose. Place in rea RETURNIN Straight	ean hose. ean couplings accord dy state and report a G HOSE TO SERV Roll Donut	ling to department guidelin ny deficiencies. TCE hose as selected by procted Twin Donut	or (Check one):					
1. 2. 3. 4.	Inspect / Cl Inspect / Cl Dry hose. Place in rea RETURNIN Straight	ean hose. ean couplings accord dy state and report a G HOSE TO SERV Roll Donut Donut	ling to department guidelin ny deficiencies. TCE hose as selected by procted Twin Donut	or (Check one): Self-Locking Twin Donut					

Evaluator (Print & Sign)

Date: